

| Weight Rating | Spindle Options | Minimum HF-SC | Beam Options | Hub Options | Bolt Pattern | Stud Sizes | Cap Options |
|---------------|------------------|-----------------------------|------------------------------------|---|--|-----------------------|---------------------------------------|
| 2200 Lbs | Straight | 10" | 1.75" RD x .188" 2" SQ x .188" | Idler | 4 on 4" 5 on 4.5" | 1/2" | Standard Cap Bearing Protector |
| 3500 Lbs. | Straight Drop | Straight 11.25" Drop 14" | 2.38" RD x .218 2" SQ x .250" | Idler Black or Zinc, Electric Manual or Self Adj Drum 10" x 2.25", Hydraulic Drum 10" x 2.25" Disc Brake Zinc or Dacromet | 5 on 4.5", 5 on 5" 5 on 5.5", 6 on 5.5" | 1/2" | Std Cap, EZ-Lube Bearing Protector |
| 4200 lbs | Straight Drop | Straight 11.25" Drop 14" | 2.88" RD x .208" | Idler Black or Zinc, Electric Manual or Self Adj Drum 10" x 2.25", Hydraulic Drum 10" x 2.25" Disc Brake Zinc or Dacromet | 5 on 4.5", 5 on 5" 5 on 5.5", 6 on 5.5" | 1/2" | Std Cap, EZ-Lube Bearing Protector |
| 5200 lbs | Straight Drop | Straight 13" Drop 15.75" | 2.88" RD x .208" | Idler Black or Zinc, Electric Manual or Self Adj 12" x 2", Hydraulic Drum 12" x 2" Disc Brake Dacromet | 6 on 5.5" | 1/2" | Std Cap, EZ-Lube Bearing Protector |
| 6000 lbs | Straight Drop | Straight 13" Drop 15.75" | 3.0" RD x .250" 2" x 3" x .250" | Idler Black or Zinc, Electric Manual or Self Adj Drum 12" x 2", Hydraulic Drum 12" x 2" Disc Brake Dacromet | 6 on 5.5" | 1/2" | Std Cap, EZ-Lube Bearing Protector |
| 7000 lbs | Straight Drop | Straight 13" Drop 15.75" | 3.0" RD x .250" 2" x 3" x .250" | Idler Black or Zinc, Electric Manual or Self Adj Drum 12" x 2", Hydraulic Drum 12" x 2" Disc Brake Dacromet | 8 on 6.5" | 1/2" 9/16" 5/8" | Std Cap, EZ-Lube Bearing Protector |
| 7400 lbs. | Straight Drop | Straight 13" Drop 15.75" | 3.0" RD x .312" | Idler Black or Zinc, Electric Manual or Self Adj Drum 12" x 2", Hydraulic Drum 12" x 2" Disc Brake Dacromet | 8 on 6.5" | 1/2" 9/16" 5/8" | Std Cap, EZ-Lube Bearing Protector |
| 8000 lbs. | Straight Drop | Straight 16" Drop 18" | 3.5" RD x .250" | Electric Self Adj Drum 12.25" x 3.38" Hydraulic Drum 12.25" x 3.38" Disc Brake Dacromet | 8 on 6.5" | 9/16" 5/8" | Std Cap, EZ-Lube Oil Bath |

Axle Beam Finishes: Std Black, Raw, Spray Galvanize, Gloss White
 Axle Lubrication: Redtak PolyPlex Lithium #2 Grease, SAE 80W-90 Gear Oil